









































How Identify Unbrako Products

PRODUCT	Marking	PRODUCT	Marking
Socket Head Cap Screw Metric : M4 to M42 Inch : 1/4" to 1" BSW		Nylock Nut M6 to M24 Grade : 8 and 10	 
		Hardened Washer (Type A) M16 to M36	
Socket Countersunk Cap Screw M5 & M24		High Strength Structural Bolt M16 to M36	 
Socket Low Head Cap Screw M5 to M20		High Strength Structural Nut M16 to M36	 
Socket Head Shoulder Screw M6 to M24		High Strength Structural Washer	
Button Head Socket Screw M5 to M12		Track Shoe Bolt and Square Nut Metric : M16 to M27 Inch : 5/8" to 1"	 
Flange Button Head Socket Screw M5 to M10			
Hexagon Wrench Set Metric : 4 A/F to 32 A/F Inch : 5/32" A/F to 3/4" A/F		Direct Tension Indicator Washer M16 to M27	
		Stainless Steel Socket Head Cap Screw M5 to M30	 
Durlok Bolt & Nut M6 to M20	 	Stainless Steel Hex Head Bolt/Screws M5 to M30 SS-304/316	 
Hex Head Bolt/Screw Metric : M5 to M48 Inch : All Sizes	 	Stainless Steel Hex Nut M5 to M30 SS-304/316	 
	  	Stainless Steel Plain Washer	 
Hex Nut Metric : M6 to M72, Inch : 1/4" to 1 1/2" Grade 8 - UNC	 	Studbolt and Nuts Metric : M12 to M56 Inch : 1/2" to 2 1/4"	 
			

According to stamping area on the Product Unbrako/U-130 will be used

Note : "X" marking on SHCS is the internal coding for product traceability, it can be changed with any alphabet.

All Products of sizes less than M5 or 1/4" no head marking due to space constraint

Unbrako reserves the right to interchange U, UNB, and UNBRAKO head markings to take account of tooling & equipment capabilities and raw material variations. Head Marking Specifications were correct at time of publication but are subject to change without notice at Unbrako discretion.